


204503-1 Product Details



204503-1



[Active](#)

Subminiature D Pin/Socket Connectors for MIL-C-24308 and MIL-C-39029

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

Product Highlights:

- Connector
- Product Series = 90
- Density = High
- Terminate To Wire
- Number of Positions = 26

[View all Features](#) | [Find Similar Products](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [AMPLIMITE PLUG FOR PIN CONTACTS HI-DENSITY D CONNECT...](#) (PDF, English)

Catalog Pages/Data Sheets:

- [AEROSPACE & DEFENSE](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- [AMPLIMITE* HIGH DENSITY 22 \(HD-22\) CONNECTORS](#) (PDF, English)

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version P)
- [3D Model](#) (IGES, Version P)
- [3D Model](#) (STEP, Version P)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector
- [Product Series](#) = 90
- [Number of Positions](#) = 26
- [Gender](#) = Plug
- [Shell Size](#) = 2
- [Shell Material](#) = Steel
- [Wire Termination Type](#) = Crimp
- Mounting Hole Diameter (mm [in]) = 3.05 [.120]
- Comment = Size 22 sockets supplied with receptacles are loose piece.; "F" is stamped on connectors following M24308 part number as required. "F" designates cadmium shell plating.

Body Related Features:

- [Blindmate](#) = No
- [Non-Magnetic](#) = No
- [Pins](#) = Without
- [Rear Grommet](#) = No
- [Power/Signal/Coax Combination](#) = No
- [Shell Plating](#) = Cadmium
- Mount Style = Mounting Holes
- Retention Clip Material = Stainless Steel

Contact Related Features:

- [Contact Size](#) = 22
- [Contact Style](#) = Crimp Snap-in

Configuration Related Features:

- [Density](#) = High

Industry Standards:

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M24308/4-265F
- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- NASA Qualification = No

Conditions for Usage:

- Terminate To = Wire

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved