

227222-2 Product Details



227222-2



BNC RF Connectors

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

Product Highlights:

- Connector
- Connector Type = BNC
- Jack
- Terminate To Printed Circuit Board
- PCB Mount Angle = Vertical

[View all Features](#) | [Find Similar Products](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [JACK, VERTICAL, 50 OHM, PCB, SERIES BNC](#) (PDF, English)

Catalog Pages/Data Sheets:

- [RF COAXIAL SOLUTIONS FOR COMMUNICATIONS](#) (PDF, English)
- [INTERCONNECTS FOR NETWORKING](#) (PDF, English)
- [RF COAX PRODUCTS](#) (PDF, English)

Product Specifications:

- [BNC PCB Straight and Right Angle Connectors](#) (PDF, English)

Application Specifications:

- None Available

Instruction Sheets:

- [Commercial BNC Jack Connectors f/PC Board and Panel ...](#) (PDF, English)

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version T)
- [3D Model](#) (IGES, Version T)
- [3D Model](#) (STEP, Version T)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector
- [Connector Type](#) = BNC
- [Gender](#) = Jack
- [PCB Mount Angle](#) = Vertical
- [Grade](#) = Commercial
- [PCB Height \(mm \[in\]\)](#) = 34.93 [1.375]
- [PCB Retention Feature](#) = Yes
- [Mounting Post Style](#) = Standard
- Mounting Post Length (mm [in]) = 3.48 [0.137]
- [Body Material](#) = VALOX
- [Body Insulation](#) = Without
- [Sealed](#) = No
- [Isolated](#) = No
- [Dielectric Material](#) = Polymethylpentene
- [Color](#) = Black
- Number of Ports = 1
- Solder Terminal = Without
- Comment = If an Insulating Bushing is required, see Part Number 330620.; Lockwasher and Jam Nut must be ordered separately.

Mechanical Attachment:

- Surface Mountable = No
- [Panel Attachment](#) = With
- Panel Attachment Method = Lockwasher and Nut
- Panel Attachment Style = Rear Mount

Electrical Characteristics:

- [Connector Impedance \(Ω\)](#) = 50

Body Related Features:

- [Hardware Included](#) = No
- [PCB Retention Method](#) = Hold Down Post
- [Polarized](#) = No

Contact Related Features:

- [Center Contact Material](#) = Phosphor Bronze
- [Center Contact Plating](#) = Tin-Lead

Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Conditions for Usage:

- [Terminate To](#) = Printed Circuit Board

Other:

- Brand = AMP