

404802692042 Product Details



404802692042


TE Internal Number: 3-1625931-5

Variable Resistors

 [Converted to EU RoHS/ELV Compliant](#)

Product Highlights:

- Variable Resistor
- Resistor Type = Potentiometer
- Resistance Selection = M Ω
- Resistance = 1M Ω
- Power Rating = 2.00 W

 [View 3D PDF](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • Spindle Operated Potentiometers - Type M Series - Ty... (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files: (CAD Format & Compression Information)</p> <ul style="list-style-type: none"> • 2D Drawing (DXF, Version P00K) • 3D Model (IGES, Version P00K) • 3D Model (STEP, Version P00K) 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Type = Variable Resistor • Resistor Type = Potentiometer • Resistance (Ω) = 1M • Element = Cermet • Sealed = Yes • Termination Type = PCB Terminations <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Resistance Selection (Ω) = M • Power Rating (W) = 2.00 • Tolerance (%) = 10 <p>Termination Related Features:</p> <ul style="list-style-type: none"> • Termination Post Orientation = 5.0 x 3.9 <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = M • Shaft Style = Plain, 1" • Package, Component Size = 19 	<p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Sections = Single • Adjustment Location = Top • Adjustment Style = Spindle • Operating Function = Single Turn <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C • RoHS/ELV Compliance History = Converted to comply with RoHS directive <p>Other:</p> <ul style="list-style-type: none"> • Brand = Citec