


5569264-1 Product Details



5569264-1



Active

PCB Mounted Jacks - Single Port, Multi-port and Stacked



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Jack
- Stacked Port Configuration
- 2 x 8 Jack Configuration
- Jack Type = RJ45
- Number of Positions = 8

[View all Features](#) | [Find Similar Products](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [STACKED MODULAR JACK ASSEMBLY, 2x8 PORT, 8 POSITION,...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [High Performance Modular Plugs & Jacks, PCB Mounted](#) (PDF, English)

Application Specifications:

- [Modular Jacks](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version A)
- [3D Model](#) (IGES, Version A)
- [3D Model](#) (STEP, Version A)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Jack
- [Jack Type](#) = RJ45
- [Number of Positions](#) = 8
- [PCB Mount Angle](#) = Side Entry (Right Angle)
- [PCB Mount Style](#) = Thru Hole
- [PCB Termination Type](#) = Solder
- [Shielded](#) = Yes
- [Performance Category](#) = Cat 5
- Number of Contacts Loaded = 8
- [Grounding Options](#) = Panel Ground and PCB Ground
- [Panel Stops](#) = Without
- [Keyed](#) = No
- [Profile](#) = Low
- [Color](#) = Black
- Number of Terminals Per Port = 8
- Shield Material = .010 [0.25] Copper Alloy
- PCB Thickness (mm [in]) = 1.57 [0.062]

Mechanical Attachment:

- [Jack Configuration](#) = 2 x 8
- [Panel Attachment](#) = Without

Termination Related Features:

- [Solder Tail Contact Plating](#) = Tin over Nickel
- Grounding Clips = Without

Body Related Features:

- Port Configuration = Stacked
- [Inverted Jack Face](#) = No
- [LED](#) = Without
- Shield Plating = Tin over Copper
- Number of PCB Ground Tabs = 6
- [PCB Tail Length \(mm \[in\]\)](#) = 3.56 [0.140]
- Grounding Tab Plating = Tin over Copper

Contact Related Features:

- [Contact Mating Area Plating](#) = Gold (50) over Nickel (50)
- Contact Material = Phosphor Bronze
- PCB ACTION PIN Grounds = Without

Housing Related Features:

- Housing Material = Polyester (PCT)
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved