

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

My Account

- [Sign In](#)
- [Register](#)


Customer Support

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [FASTON Electrical Quick Connects](#) > [Product Feature Selector](#) > Product Details

60249-1 Product Details


Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



60249-1



[Active](#)

Multiple Circuit Housings with Tabs & Receptacles Including FASTIN-FASTON

Quick Links



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Receptacle
- Tab Fit = 6.35 x 0.81 mm
- Wire Range = (2) 1.25-1.40; [(2) 16] mm [AWG], 1.25-3.00² [16-12] mm [AWG]
- Insulation Diameter = (2) 3.30 [.130] Max. mm [in], 4.06-5.33 [.160-.210] mm [in]
- Receptacle Style = Straight

[View all Features](#) | [Find Similar Products](#)

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [RECEPTACLE, FASTIN-FASTON, 6.35 \[.250\] SERIES](#) (PDF, English)

Catalog Pages/Data Sheets:

- [FASTIN_FASTON_Product_Line](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- [FASTIN-FASTON Tabs, Receptacles, and Housings](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version E)
- [3D Model](#) (IGES, Version E)
- [3D Model](#) (STEP, Version E)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- [Product Type](#) = Receptacle
- [Tab Fit \(mm \[in\]\)](#) = 6.35 x 0.81 [.250 x .032]
- [Insulation Diameter \(mm \[in\]\)](#) = (2) 3.30 [.130] Max., 4.06-5.33 [.160-.210]
- [Receptacle Style](#) = Straight
- [Wire/Cable Type](#) = Regular Wire
- [Finish](#) = None
- [Material](#) = Brass
- [Insertion Force](#) = Normal
- [Insulation Support](#) = With
- [Crimp Type](#) = "F"
- FASTON = Yes
- For Housing Type = Single
- CSA Certified = Yes

Body Related Features:

- [Wire Range \(mm \[AWG\]\)](#) = (2) 1.25-1.40; [(2) 16], 1.25-3.00² [16-12]
- Stock Thickness (mm [in]) = 0.41 [0.016]
- UL Rating = Recognized

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- [Packaging Method](#) = Strip

Other:

- Line = FASTIN-FASTON .250
- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved