

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

## . [My Account](#)


- [Sign In](#)
- [Register](#)

## . [Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [PCB Connectors - Wire to Board - Power](#) > [Product Feature Selector](#) > Product Details

# 640250-5 Product Details



**640250-5**

[Active](#)

[View 3D PDF](#)

**MTA, CST-100 II, MT-6 and SL Connectors and Headers**



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- SL-156 Housings
- Number of Positions = 5
- Mating Type = Receptacle
- Wire-to-Board Application
- 3.96 mm Contact Centerline Spacing

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [View Mating Products \(84\)](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- [housing with locking ramp, sl-156](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- [MTA-100 AND MTA-156 CONNECTORS AND HEADERS, CST-100 ...](#) (PDF, English)

**Product Specifications:**

- [Connector, SL 156](#) (PDF, English)
- [Connector, Hooded SL 156](#) (PDF, English)
- [Connector, Hooded SL 156, Tin](#) (PDF, English)

**Application Specifications:**

- [SL 156 Contacts and Housings](#) (PDF, English)

**Instruction Sheets:**

- None Available

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version U)
- [3D Model](#) (IGES, Version U)
- [3D Model](#) (STEP, Version U)

**Additional Information:**

- [Product Information](#)
- [Product Line Information](#)

**Additional Product Images:**

- [Product Photo](#)

**Related Products:**

- [Tooling](#)
- [Mating Products \(84\)](#)

[List all Documents](#)

**Product Features (Please use the Product Drawing for all design activity)**

**Product Type Features:**

- [Product Type](#) = SL-156 Housings
- [Number of Positions](#) = 5
- [Mating Type](#) = Receptacle
- [Wire Termination Type](#) = Crimp
- [Mating Polarization](#) = Without
- [Mating Connector Lock](#) = With
- [Four Points of Contact](#) = Without
- [Shrouded](#) = No
- [Mounting Ears](#) = Without
- Mating Connector Lock Type = Locking Ramp
- Comment = Recommended contact: Part No. 640252-1,-2 and Part No. 770476-1,-2.

**Mechanical Attachment:**

- [Panel Attachment](#) = Without
- Wire Insulation Diameter Size = Standard

**Body Related Features:**

- Cable Exit Angle = 180°

**Contact Related Features:**

- [Contact Centerline Spacing \(mm \[in\]\)](#) = 3.96 [0.156]

**Housing Related Features:**

- Housing Color = White
- Housing Flammability Rating = UL 94V-0
- Housing Material = Nylon

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

**Operation/Application:**

- [Application](#) = Wire-to-Board

**Other:**

- Brand = AMP