

Power Toggle Switches

Quick Links

No Image Available



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

1520228-4
(7360K8)

TE Part Number: 1520228-4



[Active](#)



[Add to Part List](#)

Product Highlights:

- Double Pole - Single Throw Configuration (Pole-Throw)
- Toggle Length = 17.04 mm
- Toggle Style = Baton
- Bushing Length = 11.50 mm
- Termination Type = Screw-In Terminal

[View all Features](#) | [Find Similar Products](#)

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [20 AMP 125V AC/DC, 10 AMP 250V AC/DC, 1 1/2 HP 125V...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version B)
- [3D Model](#) (IGES, Version B)
- [3D Model](#) (STEP, Version B)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Configuration (Pole-Throw) = Double Pole - Single Throw
- Termination Type = Screw-In Terminal

Electrical Characteristics:

- UL/CSA 125V Current Rating (Amps.) = 20
- UL/CSA 250V Current Rating (Amps.) = 10
- UL/CSA 125V Horse Power Rating (hp) = 1.50
- UL/CSA 250V Horse Power Rating (hp) = 1.50

Housing Related Features:

- Toggle Length (mm [in]) = 17.04 [0.671]
- Toggle Style = Baton

Configuration Related Features:

- Bushing Length (mm [in]) = 11.50 [0.453]

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not reviewed for lead free solder process
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = Alcoswitch