


87191-1 Product Details



87191-1

TE Internal Number: 87191-1

 [Active](#)

Contacts-AMPMODU Machine Applied

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Contact Type = Locking Clip
- Post Size = 0.64 [.025] mm [in]
- Wire Range = 0.05-0.09² [30-28] mm [AWG]
- Wire Insulation Diameter = .74 - .99 mm
- Phosphor Bronze Contact Base Material

[View all Features](#)

Documentation & Additional Information

Product Drawings:

- [CONTACT - LOCKING CLIP FOR 0.64 \[.025\] SQUARE POST](#) (PDF, English)

Catalog Pages/Data Sheets:

- [AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- [Locking Clip 0.64-mm \(.025-in.\) Square Contacts and ...](#) (PDF, English)

Instruction Sheets:

- [AMPMODU Locking Clip Contacts and Housings for 0.64m...](#) (PDF, English)
- [Hand Crimping Tool 90295-1](#) (PDF, English)

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version J)
- [3D Model](#) (IGES, Version J)
- [3D Model](#) (STEP, Version J)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Post Size \(mm \[in\]\)](#) = 0.64 [.025]
- [Wire Insulation Diameter \(mm \[in\]\)](#) = 0.74 – 0.99 [0.029 – 0.039]
- With Insulation Support = Yes
- Wire Termination Type = Crimp
- Comment = These contacts must be crimped in accordance with AMP Specification No. 114-25006 in order to function properly in a connector housing.; Extraction Tool No. 91084-1 is used for removing individual contacts from connector housings and for detaching contacts from mating posts.; (*) For use with Model "K" machines. Call the Technical Assistance Center (1-800-522-6752) for part numbers of applicators for use with Model "G" machines, as well as other bench machines and fully automatic AMPOMATOR lead making machines.

Mechanical Attachment:

- Contact Spring Material = Stainless Steel

Contact Related Features:

- [Contact Type](#) = Locking Clip
- [Contact Base Material](#) = Phosphor Bronze
- [Contact Mating Area Plating Material](#) = Gold (30) over Nickel (50)
- Contact Shape = Square
- Approved Standards = UL E28476

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Operating Temperature (°C) = -65 – +105

Packaging Related Features:

- [Packaging Method](#) = Loose Piece

Electrical Characteristics:

- Contact Current Rating (Amps.) = 3
- Termination Resistance (m) = 12
- Insulation Resistance (M) = 5,000
- Dielectric Withstanding Voltage (V) = 750

Termination Related Features:

- Solder Tail Contact Plating = Gold Flash over Nickel (50)

Body Related Features:

- [Wire Range \(mm \[AWG\]\)](#) = 0.05-0.09² [30-28]

Other:

- Brand = AMP