


KHU-17A11-120 Product Details



KHU-17A11-120

TE Part Number: 2-1393123-4



Active



Add to Part List

Industrial Relays (General Purpose)



[Always EU RoHS compliant but not ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- KHU Series
- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- Contact Current Rating = 3 Amps.
- Monostable Coil Magnetic System
- Input Voltage = 120 VAC

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [KHA General Purpose Dry Circuit to 5A Multicontact A...](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [PCB Layout](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Termination Type](#) = Solder Terminals

Electrical Characteristics:

- [Contact Current Rating \(Amps.\)](#) = 3
- [Input Voltage \(VAC\)](#) = 120
- [Coil Resistance \(•\)](#) = 3900
- [Actuating System](#) = AC
- [Coil Power, Nominal \(VA\)](#) = 1.20

Body Related Features:

- Series = KHU
- Polarized = No

Contact Related Features:

- [Mounting Options](#) = PC Board, Socket
- [Enclosure](#) = Dust Cover
- FCC Part 68 Isolation = No
- Relay Type = General
- [Contact Material](#) = Silver
- Approx. Dimensions (L x W x H) (mm [in]) = 28.20 x 21.80 x 34.90 [1.111 x .858 x 1.375]
- Wiring Diagram = 4 Form C
- Approved Standards = UL Recognized, CSA Certified

Configuration Related Features:

- [Contact Arrangement](#) = 4 Form C, 4PDT, 4 C/O
- [Coil Magnetic System](#) = Monostable
- [Coil Suppression Diode](#) = Without
- [Coil Selection Criteria](#) = Nominal Voltage
- Coil Latching = Without
- [LED Indicator](#) = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS not ELV compliant

Other:

- Brand = Potter & Brumfield