

Pushbutton Switches

Quick Links



MSPF101BC0

TE Part Number: 8-1437567-9



[Active](#)



[Add to Part List](#)



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Switch - Mechanical
- Not Tactile
- Two Circuit Configuration (Pole-Throw)
- Contact Rating = 0.5A
- Operating Function = Normally Open Normally Closed, Momentary

[View all Features](#) | [Find Similar Products](#)

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [PUSH BUTTON MOMENTARY \(MSPF-101BC SERIES\)](#) (PDF, English)

Catalog Pages/Data Sheets:

- [ALCOSWITCH PRODUCTS](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch - Mechanical
- Tactile = No
- Configuration (Pole-Throw) = Two Circuit
- Mount Angle = Vertical
- Termination Type = Wire Lugs
- Actuator Style = Round
- Comment = Versatile front or rear entry, with hardware supplied.

Electrical Characteristics:

- Contact Rating = 0.5A

Body Related Features:

- [Series](#) = MSPF
- Mount Style = Panel
- Actuator Length (mm [in]) = 6.50 [0.256]
- Actuator Profile = Extended
- Actuator Color = Black
- Bushing Diameter = 15/32
- Case Material = Thermoset
- Actuator Material = Thermoplastic

Contact Related Features:

- Contact Plating = Silver

Housing Related Features:

- Process Sealed = No
- Low Profile = No
- Bushing Style = Threaded

Configuration Related Features:

- Operating Function = Normally Open Normally Closed, Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Hand solderable with lead free solder
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Temperature Rating = Standard

Packaging Related Features:

- Packaging Method = Loose Piece

Other:

- Brand = Alcoswitch