

## ROX3SJ390R Product Details



**ROX3SJ390R**

TE Internal Number: 4-1625892-4

 [Active](#)

### Fixed Resistors

 [Converted to EU RoHS/ELV Compliant](#)  
([Statement of Compliance](#))

### Product Highlights:

- Fixed Resistor
- Resistor Type = Power Resistor
- Resistance Selection = <1K  $\Omega$
- Resistance = 390  $\Omega$
- Power Rating = 3.00 W

[View all Features](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Flame Proof Power Metal Oxide Film Resistors - Type ...</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p style="text-align: right;"><a href="#">List all Documents</a></p>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>
Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• Product Type = Fixed Resistor</li> <li>• Resistor Type = Power Resistor</li> <li>• <a href="#">Resistance (<math>\Omega</math>)</a> = 390</li> <li>• <a href="#">Element</a> = Metal Oxide</li> <li>• <a href="#">Termination Type</a> = Tinned Copper Leads</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Resistance Selection (<math>\Omega</math>)</a> = &lt;1K</li> <li>• <a href="#">Power Rating (W)</a> = 3.00</li> <li>• <a href="#">Tolerance (%)</a> = 5</li> <li>• <a href="#">Package Type</a> = Ammo Packed</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Series</a> = ROX</li> <li>• <a href="#">Mount Style</a> = Axial Leaded</li> <li>• <a href="#">Package, Component Size</a> = 15 x 5.5</li> </ul>	<p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>• RoHS/ELV Compliance History = Converted to comply with RoHS directive</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Temperature Coefficient (ppm/°C)</a> = <math>\pm 300</math></li> </ul> <p><b>Operation/Application:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Application</a> = Power</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Neohm</li> </ul>