



[My Cart](#) | [My Part Lists](#) | [Sign In](#) | [Register](#)

[English \(Change\)](#)



Search by Keyword or Part #

[Leave BETA Search](#)

## SMF26K8JT Product Details

### Have a Question?

Chat with a Product Information Specialist



**SMF26K8JT**

TE Internal Number: 3-1879011-7

Active

#### Fixed Resistors

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Fixed Resistor Temporary List (1)
- Resistor Type = Power Resistor
- Resistance Selection = K  $\Omega$
- Resistance = 6.8K  $\Omega$
- Power Rating = 2.00 W

[View all Features](#)

#### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#)   [Request Sample](#)   [Find Similar Products](#)   [Buy Product](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li><a href="#">SMD Moulded Power Resistor - Type SM Series - Tyco E...</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li><a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li><a href="#">Tooling</a></li> </ul>

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>Product Type = Fixed Resistor</li> <li>Resistor Type = Power Resistor</li> <li><a href="#">Resistance (<math>\Omega</math>)</a> = 6.8K</li> <li><a href="#">Element</a> = Metal Film</li> <li>Termination Type = Solder</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li><a href="#">Resistance Selection (<math>\Omega</math>)</a> = K</li> <li><a href="#">Power Rating (W)</a> = 2.00</li> <li><a href="#">Tolerance (%)</a> = 5</li> <li><a href="#">Package Type</a> = Taped and Reeled</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li><a href="#">Series</a> = SM</li> <li><a href="#">Mount Style</a> = Surface Mount</li> <li><a href="#">Package, Component Size</a> = 4.0 x 6.7</li> </ul>	<p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li><a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li><a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>RoHS/ELV Compliance History = Always was RoHS compliant</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li><a href="#">Temperature Coefficient (ppm/°C)</a> = <math>\pm 100</math></li> </ul> <p><b>Operation/Application:</b></p> <ul style="list-style-type: none"> <li><a href="#">Application</a> = Power</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>Brand = CGS</li> </ul>



#### Corporate Information

[Who We Are](#)

#### Quick Links

[Check Distributor Inventory](#)

#### Customer Support

[Email or Chat with Us](#)

#### Sign up for our eNewsletter

Enter your email address

[Investors](#)

[Cross Reference](#)

[Find a Phone Number](#)

[News Room](#)

[Find Documents & Drawings](#)

[Search Knowledge Base](#)

[Supplier Portal](#)

[Product Compliance Support Center](#)

[Manage Your Account](#)

[Careers](#)

[Site Map](#)

Follow us on:

