



## TT41NGPC9T1/4

TE Part Number: 6-1437562-8



Active



Add to Part List

## Toggle Switches



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- TT (Tiny) Series
- Four Pole - Double Throw Configuration (Pole-Throw)
- Current Rating = 0.4 VA Amps.
- Mount Style = Through-Hole
- Termination Type = Printed Circuit, Vertical

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- None Available

### Catalog Pages/Data Sheets:

- [ALCOSWITCH PRODUCTS](#) (PDF, English)

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Additional Product Images:

- [Product Photo](#)
- [Dimensional Drawing](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Configuration (Pole-Throw) = Four Pole - Double Throw
- Termination Type = Printed Circuit, Vertical
- Color = Black

### Electrical Characteristics:

- Current Rating (Amps.) = 0.4 VA

### Termination Related Features:

- Seal Type = Terminal Seal (epoxy)

### Body Related Features:

- Series = TT (Tiny)
- Mount Style = Through-Hole
- Flammability Rating = UL 94V-0

### Contact Related Features:

- Contact Plating = Gold over Nickel
- Contact Material = Copper Alloy

### Housing Related Features:

- Toggle Style = Baton Long
- Toggle Length (mm [in]) = 10.40 [0.410]
- Process Sealed = No
- Bushing Style = Threaded
- Bushing Type = 1/4-40

### Configuration Related Features:

- [Operating Function](#) = On None On

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

### Other:

- Brand = Alcoswitch