

Single Phase Bridge (Power Modules), 25/35 A


MB

FEATURES

- Universal, 3 way terminals:
Push-on, wrap around or solder
- High thermal conductivity package, electrically insulated case
- Center hole fixing
- Excellent power/volume ratio
- UL E300359 approved
- Nickel plated terminals solderable using lead (Pb)-free solder; Solder Alloy Sn/Ag/Cu (SAC305); Solder temperature 260 to 275 °C
- RoHS compliant
- Designed and qualified for industrial level


**RoHS
COMPLIANT**

PRODUCT SUMMARY

$I_{T(AV)}$	25/35 A
-------------	---------

DESCRIPTION

A range of extremely compact, encapsulated single phase bridge rectifiers offering efficient and reliable operation. They are intended for use in general purpose and instrumentation applications.

MAJOR RATINGS AND CHARACTERISTICS

SYMBOL	CHARACTERISTICS	26MB-A	36MB-A	UNITS
I_o		25	35	A
	T_c	65	60	°C
I_{FSM}	50 Hz	400	475	A
	60 Hz	420	500	
I^2t	50 Hz	790	1130	A^2s
	60 Hz	725	1030	
V_{RRM}	Range	200 to 1200		V
T_j		- 55 to 150		°C

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS

TYPE NUMBER	VOLTAGE CODE	V_{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V	V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V	I_{RRM} MAXIMUM AT T_j MAXIMUM
26MB..A 36MB..A	20	200	275	2
	40	400	500	
	60	600	725	
	80	800	900	
	100	1000	1100	
	120	1200	1300	

MB Series

Vishay High Power Products

Single Phase Bridge
(Power Modules), 25/35 A



FORWARD CONDUCTION


PARAMETER	SYMBOL	TEST CONDITIONS			26MB-A	36MB-A	UNITS	
Maximum DC output current at case temperature	I_O	Resistive or inductive load			25	35	A	
		Capacitive load			20	28		
					65	60		
Maximum peak, one-cycle non-repetitive forward current	I_{FSM}	$t = 10 \text{ ms}$	No voltage reapplied	Initial $T_J = T_J$ maximum	400	475	A	
		$t = 8.3 \text{ ms}$			420	500		
		$t = 10 \text{ ms}$	100 % V_{RRM} reapplied		335	400		
		$t = 8.3 \text{ ms}$			350	420		
Maximum I^2t for fusing	I^2t	$t = 10 \text{ ms}$	No voltage reapplied	Initial $T_J = T_J$ maximum	790	1130	A ² s	
		$t = 8.3 \text{ ms}$			725	1030		
		$t = 10 \text{ ms}$	100 % V_{RRM} reapplied		560	800		
		$t = 8.3 \text{ ms}$			512	730		
Maximum $I^2\sqrt{t}$ for fusing	$I^2\sqrt{t}$	I^2t for time $t_x = I_2\sqrt{t} \times \sqrt{t_x}$; $0.1 \leq t_x \leq 10 \text{ ms}$, $V_{RRM} = 0 \text{ V}$			5.6	11.3	kA ² /s	
Low level value of threshold voltage	$V_{F(TO)1}$	$(16.7 \% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, T_J maximum			0.76	0.79	V	
High level value of threshold voltage	$V_{F(TO)2}$	$(I > \pi \times I_{F(AV)})$, T_J maximum			0.92	0.96		
Low level forward slope resistance	r_{t1}	$(16.7 \% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, T_J maximum			6.8	5.8	mΩ	
High level forward slope resistance	r_{t2}	$(I > \pi \times I_{F(AV)})$, T_J maximum			5.0	4.5		
Maximum forward voltage drop	V_{FM}	$T_J = 25 \text{ }^\circ\text{C}$, $I_{FM} = 40 \text{ A}_{pk}$ (26MB)	$t_p = 400 \mu\text{s}$	1.11	1.14	V		
Maximum DC reverse current	I_{RRM}	$T_J = 25 \text{ }^\circ\text{C}$, per diode at V_{RRM}						
RMS isolation voltage base plate	V_{INS}	$f = 50 \text{ Hz}$, $t = 1 \text{ s}$			10		μA	
					2700		V	

THERMAL AND MECHANICAL SPECIFICATIONS


PARAMETER	SYMBOL	TEST CONDITIONS			26MB-A	36MB-A	UNITS
Junction and storage temperature range	T_J , T_{Stg}				- 55 to 150		°C
Maximum thermal resistance junction to case per bridge	R_{thJC}				1.7	1.2	K/W
Maximum thermal resistance, case to heatsink	R_{thCS}	Mounting surface, smooth, flat and greased			0.2		
Approximate weight					20		g
Mounting torque ± 10 %		Bridge to heatsink			2.0		Nm

ORDERING INFORMATION TABLE

Device code	36	MB	120	A	
	1	2	3	4	
[1]	- Current rating code	26 = 25 A (average) 36 = 35 A (average)			
[2]	- Circuit configuration:	MB = Single phase european coding			
[3]	- Voltage code x 10 = V_{RRM}				
[4]	- Diode bridge rectifier: A = 26 MB, 36 MB series				

CIRCUIT CONFIGURATION


D-34

DIMENSIONS in millimeters (inches)


Suggested plugging force:
200 N max; axially applied to fast-on terminals