



## Model #: 4SPDX

### Waber-by-Tripp Lite Power Strip - Multiple outlet strip with relocatable power tap



#### Highlights

- 4 outlets
- 7.38 in. length
- Lighted master switch
- All-metal housing

#### Description

T□  
applications□  
installation in a wi□  
devices to a sing□  
power. Featu□  
Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 4 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

#### Applications

- Offers multiple o□  
ideal for distributing alternate waveform UPS or generator power to protected equipment.

#### Package Includes

- 4SPDX Power Strip
- Warranty information
- Instruction manual

#### Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 4 NEMA 5-15R output receptacles with 1.520-in. center-to-center spacing
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting support permanent installation on a wide variety of surfaces
- UL1363 (USA), cUL (Canada)
- 15A power handling capacity
- 6-ft. AC line cord

Lifetime warranty

## Specifications

| <b>SYSTEM OVERVIEW</b>            |  |
|-----------------------------------|--|
| Voltage compatibility             | 120VAC   |
| Frequency compatibility           | 50/60 Hz   |
| <b>OUTPUT</b>                     |  |
| Output volt amp capacity (amps)   | 15A  |
| Outlet quantity / type            | 4 NEMA 5-15R   |
| Outlet orientation                | Single row of 4  |
| Outlet spacing                    | 1.520 in.  |
| <b>INPUT</b>                      |  |
| Input connection type             | NEMA 5-15P   |
| Input cord length (ft.)           | 6  |
| Input cord length (m)             | 1.8288   |
| Recommended Electrical Service    | 15A 120V   |
| <b>LEDS ALARMS &amp; SWITCHES</b> |  |
| Switches                          | Lighted combination switch / circuit breaker                   |
| <b>PHYSICAL</b>                   |  |
| Unit Dimensions (HWD/in)          | 7.5 x 2.5 x 1.5  |
| Unit Dimensions (HWD/cm)          | 19.1 x 6.4 x 3.8   |
| Material of construction          | Metal  |
| Integrated keyhole mounting tabs  | Keyhole mounting tabs enable mounting to a variety of surfaces |
| Receptacle Color                  | Beige  |
| AC line cord color                | Beige  |
| <b>CERTIFICATIONS</b>             |  |
| UL1363 (Power Tap)                | UL1363   |
| cUL / CSA (Canada)                | cUL  |
| <b>WARRANTY</b>                   |  |
| Product warranty                  | Lifetime   |