

#### **PRODUCTS**

**CROSS-REFERENCE** 



# **Euro-Style Terminal Blocks**

TYPE 3-DIN-46284-ST (-HDS) 13 mm spacing - 3 poles **Inventory Check** 

Series	Download PDF	3D Model	Can plug with	How to order	Print
--------	--------------	----------	---------------	--------------	-------



Front view



Top view

# **Description**


The porcelain molding for this terminal block was designed to provide excellent resistance to high temperatures and the ability to allow high current voltage ratings.

The DIN-46284 standard pertains to two- and threepole appliance terminals with 380V AC and 440V DC. They are supplied with a stainless steel wire protector to prevent damage to stranded wiring. For the 2 pole version, please see part # 2-DIN-46284-ST.

Recommended mounting hardware: M4 cheese head screw (#8-32 fillister head screw)

- Ceramic Terminal Block
- Medium Duty
- With Clamping Screws
- With Mounting Holes

### **Technical Data**



Dimensions: mm (in.)

Length of Connector (L) L = 20 (0.79) 2 pole / 34 (1.33) 3 pole

When locating connector, allow 0.5 mm clearance around it for process-induced variations.

#### **Approval Information**

CSA File No.LR24322



Rating	Current(A)	Voltage(V)	Application group	AWG
UL				
CSA	20	300	B,C,D,E	18-12

# **Screw Tightening Torque:**

4.5

#### International Approvals:





Center to Center Spacing: 13 mm (0.512 in.)

Nominal Cross Section: 2.5 mm<sup>2</sup> (3874 mils<sup>2</sup>)

Wire Stripping Length: 7 mm (0.28 in.)

Material

Molding: Glazed porcelain KER 111, DIN 40685,

color white

Temperature upper limit: 200°C (392°F) Terminal Body: Nickel plated brass Wire Protector: Stainless steel

Screw: M3, Zinc plated blue passivated, steel

substrate

Top of page

How to order

Item 3-DIN-46284-ST (-HDS)

**Options** 

**BS**: Brass Screws

G05: Gold Plating (5 micro inches)G30: Gold Plating (30 micro inches)S30: Silver Plating (30 micro inches)

Ordering Note: Plated component: terminal body For 2-pole version see part #2-

DIN-46284-ST

WIRE PROTECTOR: with: - HDS

**3** -DIN-46284-ST

Request sample Request quote

Quantity

**Accessories** 

Add to shopping cart

2008, WECO Electrical Connectors Inc.

ISO 9001 registered quality management system