



Model #: UL603CB-6

Waber-by-Tripp Lite Power Strip - Multiple outlet strip with relocatable power tap



Highlights

- 4 outlets
- 6 ft. cord
- 7.38" length
- All metal housing
- Lighted on/off switch with locking safety cover

Description

The W□ applications.□ for installation in a wi□ devices to a sing□ power. Feature□ breaker and attractive blue/gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 4 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

Applications

- Offers multiple o□ ideal for distributing alternate waveform UPS or generator power to protected equipment.

Package Includes

- UL603CB-6 Power Strip
- Warranty information
- Instruction manual

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 4 NEMA 5-15R output receptacles with 1.25 inch center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity with circuit breaker
- Lifetime warranty

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Outlet quantity / type	4 NEMA 5-15R
Outlet orientation	Single row of 4
Outlet spacing	1.25 in.
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	6
Input cord length (m)	1.8288
Recommended Electrical Service	15A 120V
LEDS ALARMS & SWITCHES	
Switches	Lighted 2 position switch controls power to all outlets
Locking switch cover	Transparent on/off switch cover prevents accidental turn-off
PHYSICAL	
Unit Dimensions (HWD/in)	7.38 x 2.5 x 1.5
Unit Dimensions (HWD/cm)	18.75 x 6.4 x 3.8
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs enable mounting to a variety of surfaces
Receptacle Color	Black
AC line cord color	Black
CERTIFICATIONS	
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product warranty	Lifetime