

[Search](#)  
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

## Network SurgeArrest 8 Outlet 120V

Advanced Surge Protection for Network Business Systems.

Includes: Cord Management Straps, User Manual



[+] More Images

- [Compare Models](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)


**Additional Information**  
[Product Overview](#)  
[User Manual & Installation Guides](#)  
[Product Distribution](#)

## Technical Specifications

### Output

Number of Outlets	8
Receptacle Style	NEMA 5-15R

### Input

Nominal input voltage	120V
Input frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connection Type	NEMA 5-15P 
Maximum Line Current per phase	15A

### Features:

- Always on Outlets
- Catastrophic Event Protection
- Cord Management
- Lightning and Surge Protection
- Protection working indicator
- Right Angle Plug
- Site wiring fault indicator
- Transformer Block Spacing

### Surge Protection and Filtering

Surge energy rating	480 Joules
eP Joule Rating	3420
EMI/RFI Noise rejection (100 kHz to 10 mHz)	70 dB
Peak Current Normal Mode	13 kAmps
Peak Current Common Mode	26 kAmps
Dataline protection	--
Data Lines Protected (multi-line only)	--
Let Through Voltage Rating	< 40

### Physical

Net weight	1.90 lbs. ( 0.86 kg)
Maximum height	1.75 inches ( 44 mm)
Maximum width	8.00 inches (203 mm)

Maximum depth	5.75 inches (146 mm)
Shipping Weight	2.20 lbs. ( 1.00 kg)
Shipping Height	2.00 inches ( 51 mm)
Shipping Width	12.50 inches (318 mm)
Shipping Depth	6.25 inches (159 mm)
Master Carton Units	12.00
Master Carton Weight	29.50 lbs.
SCC Codes	10731304000843
Color	Beige
Units per Pallet	600.00

#### Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

#### Conformance

Approvals	CSA,UL 1283,UL 1363,UL 1449
Standard warranty	Lifetime
UL 1449 TVSS Rating	330 V

[Copyright](#) © American Power Conversion Corp., all rights reserved  
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)